

Neon 35

35Litre Ultrasonic Cleaning System



The Neon Series enhances your ultrasonic cleaning activities, delivering outstanding performance from one small footprint. The integral recirculation system ensures minimal fluid contamination even after cleaning, reducing running costs and improving component cleanliness.

Outstanding Cleaning Quality

Frequency Leap Technology ensures homogenous cavitation through the tank. The filtered cleaning fluid removes contaminants and minimises drag through.

Fully Integrated System

The Neon Series incorporates an overflowweir, pump and filtration in one small footprint. Its clever modular design allows easy retrofitting of additional wash, rinse and drying stages as required.

Compatibility and Durability

All wetted parts are 316 stainless steel, maximising chemical compatibility and system longevity.

Environmentally Friendly, Cost Saving

Running costs and waste are reduced by the filtered and recirculated cleaning fluid, using less water and detergent than standard ultrasonic cleaners.







Standard Features:

- "Overflow-weir and recirculation system
- "Stainless steel pump and twin filtration
- "2mm thick 316 stainless steel tank
- "Multi-stage modular compatibility
- "Support struts for basket draining
- "Frequency Leap Technology
- "Split level program security
- "Integrated Jetting System
- "Tri-program heat control
- "Fluid level protection
- " Digital LCD control
- "Lid holder

Eastgate Business Park Tel: +44 (0) 845 330 4236
Wentloog Avenue Fax: +44 (0) 845 330 4231
Cardiff CF3 2EY Email: admin@ultrawave.co.uk
United Kingdom Web: www.ultrawave.co.uk



Neon 35 35Litre Ultrasonic Cleaning System

Construction Case 304 Stainless Steel

Construction Tank 316 Stainless Steel (2mm)

Control Digital (Time, Temperature, Recirculation)

Overall Dimensions 685 x 600 x 905mm (WxDxH)

Internal Tank Dimensions including weir 500 x 400 x 280mm (WxDxH)

Working Tank Dimensions 500 x 300 x 230mm (WxDxH)

425 x 255 x 195mm (WxDxH) **Basket Dimensions**

35Litres Working Capacity

Ultrasonic Power 500W

Ultrasonic Power (per litre) 14.3W/Litre

Operating Frequency 32 - 38KHz Frequency Leap

Ambient - 80°C Maximum Heating Capacity

Heater Power 1000W

Timer 0 - 80 minutes

Mains Connection 230Vac, 13A or 16A plug

Drain Outlet 34" BSP Stainless Steel

Pump and Filtration System 316 Stainless Steel

304 Stainless Steel Lid

Basket 304 Stainless Steel

Warranty 3 Years



Tel:



Eastgate Business Park Wentloog Avenue Cardiff CF3 2EY United Kingdom

+44 (0) 845 330 4236 +44 (0) 845 330 4231 Fax: Email: admin@ultrawave.co.uk Web: www.ultrawave.co.uk